

O-RING STANDARD SIZE (AS568)

AS 568A UNIVERSAL DASH NUMBERS	NOMINAL SIZE			STANDARD O-RING SIZE				METRIC O-RING SIZE			
	INCHES			INCHES				MILLIMETERS			
	I.D.	O.D.	W.	I.D.	±	W.	±	I.D.	±	W.	±
-042	3¼	3¾	1/16	3.239	.024	.070	.003	82.27	0.61	1.78	0.08
-043	3½	3⅝	1/16	3.489	.024	.070	.003	88.62	0.61	1.78	0.08
-044	3¾	3⅞	1/16	3.739	.027	.070	.003	94.97	0.69	1.78	0.08
-045	4	4⅛	1/16	3.989	.027	.070	.003	101.32	0.69	1.78	0.08
-046	4¼	4¾	1/16	4.239	.030	.070	.003	107.67	0.76	1.78	0.08
-047	4½	4⅝	1/16	4.489	.030	.070	.003	114.02	0.76	1.78	0.08
-048	4¾	4⅞	1/16	4.739	.030	.070	.003	120.37	0.76	1.78	0.08
-049	5	5⅛	1/16	4.989	.037	.070	.003	126.72	0.94	1.78	0.08
-050	5¼	5¾	1/16	5.239	.037	.070	.003	133.07	0.94	1.78	0.08
-102	1/16	1/4	3/32	.049	.005	.103	.003	1.24	0.13	2.62	0.08
-103	3/32	9/32	3/32	.081	.005	.103	.003	2.06	0.13	2.62	0.08
-104	1/8	5/16	3/32	.112	.005	.103	.003	2.84	0.13	2.62	0.08
-105	5/32	11/32	3/32	.143	.005	.103	.003	3.63	0.13	2.62	0.08
-106	3/16	3/8	3/32	.174	.005	.103	.003	4.42	0.13	2.62	0.08
-107	7/32	13/32	3/32	.206	.005	.103	.003	5.23	0.13	2.62	0.08
-108	1/4	7/16	3/32	.237	.005	.103	.003	6.02	0.13	2.62	0.08
-109	5/16	1/2	3/32	.299	.005	.103	.003	7.59	0.13	2.62	0.08
-110	3/8	9/16	3/32	.362	.005	.103	.003	9.19	0.13	2.62	0.08
-111	7/16	5/8	3/32	.424	.005	.103	.003	10.77	0.13	2.62	0.08
-112	1/2	11/16	3/32	.487	.005	.103	.003	12.37	0.13	2.62	0.08
-113	9/16	3/4	3/32	.549	.007	.103	.003	13.94	0.18	2.62	0.08
-114	5/8	13/16	3/32	.612	.009	.103	.003	15.54	0.23	2.62	0.08
-115	11/16	7/8	3/32	.674	.009	.103	.003	17.12	0.23	2.62	0.08
-116	3/4	15/16	3/32	.737	.009	.103	.003	18.72	0.23	2.62	0.08
-117	13/16	1	3/32	.799	.010	.103	.003	20.30	0.25	2.62	0.08
-118	7/8	11/16	3/32	.862	.010	.103	.003	21.89	0.25	2.62	0.08
-119	15/16	1⅛	3/32	.924	.010	.103	.003	23.47	0.25	2.62	0.08
-120	1	13/16	3/32	.987	.010	.103	.003	25.07	0.25	2.62	0.08
-121	11/16	1¼	3/32	1.049	.010	.103	.003	26.64	0.25	2.62	0.08
-122	1⅛	15/16	3/32	1.112	.010	.103	.003	28.24	0.25	2.62	0.08
-123	13/16	1¾	3/32	1.174	.012	.103	.003	29.82	0.30	2.62	0.08
-124	1¼	17/16	3/32	1.237	.012	.103	.003	31.42	0.30	2.62	0.08
-125	15/16	1½	3/32	1.299	.012	.103	.003	32.99	0.30	2.62	0.08
-126	1¾	19/16	3/32	1.362	.012	.103	.003	34.59	0.30	2.62	0.08
-127	17/16	1⅝	3/32	1.424	.012	.103	.003	36.17	0.30	2.62	0.08
-128	1½	111/16	3/32	1.487	.012	.103	.003	37.77	0.30	2.62	0.08
-129	19/16	1¾	3/32	1.549	.015	.103	.003	39.34	0.38	2.62	0.08
-130	1⅝	113/16	3/32	1.612	.015	.103	.003	40.94	0.38	2.62	0.08
-131	111/16	1⅞	3/32	1.674	.015	.103	.003	42.52	0.38	2.62	0.08
-132	1 3/4	115/16	3/32	1.737	.015	.103	.003	44.12	0.38	2.62	0.08
-133	113/16	2	3/32	1.799	.015	.103	.003	45.69	0.38	2.62	0.08

O-RING STANDARD SIZE (AS568)

AS 568A UNIVERSAL DASH NUMBERS	NOMINAL SIZE			STANDARD O-RING SIZE				METRIC O-RING SIZE			
	INCHES			INCHES				MILLIMETERS			
	I.D.	O.D.	W.	I.D.	±	W.	±	I.D.	±	W.	±
-134	1 ⁷ / ₈	2 ¹ / ₁₆	3 ₃₂	1.862	.015	.103	.003	47.29	0.38	2.62	0.08
-135	1 ¹⁵ / ₁₆	2 ¹ / ₈	3 ₃₂	1.925	.017	.103	.003	48.90	0.43	2.62	0.08
-136	2	2 ³ / ₁₆	3 ₃₂	1.987	.017	.103	.003	50.47	0.43	2.62	0.08
-137	2 ¹ / ₁₆	2 ¹ / ₄	3 ₃₂	2.050	.017	.103	.003	52.07	0.43	2.62	0.08
-138	2 ¹ / ₈	2 ⁵ / ₁₆	3 ₃₂	2.112	.017	.103	.003	53.64	0.43	2.62	0.08
-139	2 ³ / ₁₆	2 ³ / ₈	3 ₃₂	2.175	.017	.103	.003	55.25	0.43	2.62	0.08
-140	2 ¹ / ₄	2 ⁷ / ₁₆	3 ₃₂	2.237	.017	.103	.003	56.82	0.43	2.62	0.08
-141	2 ⁵ / ₁₆	2 ¹ / ₂	3 ₃₂	2.300	.020	.103	.003	58.42	0.51	2.62	0.08
-142	2 ³ / ₈	2 ⁹ / ₁₆	3 ₃₂	2.362	.020	.103	.003	59.99	0.51	2.62	0.08
-143	2 ⁷ / ₁₆	2 ⁵ / ₈	3 ₃₂	2.425	.020	.103	.003	61.60	0.51	2.62	0.08
-144	2 ¹ / ₂	2 ¹¹ / ₁₆	3 ₃₂	2.487	.020	.103	.003	63.17	0.51	2.62	0.08
-145	2 ⁹ / ₁₆	2 ³ / ₄	3 ₃₂	2.550	.020	.103	.003	64.77	0.51	2.62	0.08
-146	2 ⁵ / ₈	2 ¹³ / ₁₆	3 ₃₂	2.612	.020	.103	.003	66.34	0.51	2.62	0.08
-147	2 ¹¹ / ₁₆	2 ⁷ / ₈	3 ₃₂	2.675	.022	.103	.003	67.95	0.56	2.62	0.08
-148	2 ³ / ₄	2 ¹⁵ / ₁₆	3 ₃₂	2.737	.022	.103	.003	69.52	0.56	2.62	0.08
-149	2 ¹³ / ₁₆	3	3 ₃₂	2.800	.022	.103	.003	71.12	0.56	2.62	0.08
-150	2 ⁷ / ₈	3 ¹ / ₁₆	3 ₃₂	2.862	.022	.103	.003	72.69	0.56	2.62	0.08
-151	3	3 ³ / ₁₆	3 ₃₂	2.987	.024	.103	.003	75.87	0.61	2.62	0.08
-152	3 ¹ / ₄	3 ⁷ / ₁₆	3 ₃₂	3.237	.024	.103	.003	82.22	0.61	2.62	0.08
-153	3 ¹ / ₂	3 ¹¹ / ₁₆	3 ₃₂	3.487	.024	.103	.003	88.57	0.61	2.62	0.08
-154	3 ³ / ₄	3 ¹⁵ / ₁₆	3 ₃₂	3.737	.028	.103	.003	94.92	0.71	2.62	0.08
-155	4	4 ³ / ₁₆	3 ₃₂	3.987	.028	.103	.003	101.27	0.71	2.62	0.08
-156	4 ¹ / ₄	4 ⁷ / ₁₆	3 ₃₂	4.237	.030	.103	.003	107.62	0.76	2.62	0.08
-157	4 ¹ / ₂	4 ¹¹ / ₁₆	3 ₃₂	4.487	.030	.103	.003	113.97	0.76	2.62	0.08
-158	4 ³ / ₄	4 ¹⁵ / ₁₆	3 ₃₂	4.737	.030	.103	.003	120.32	0.76	2.62	0.08
-159	5	5 ³ / ₁₆	3 ₃₂	4.987	.035	.103	.003	126.67	0.89	2.62	0.08
-160	5 ¹ / ₄	5 ⁷ / ₁₆	3 ₃₂	5.237	.035	.103	.003	133.02	0.89	2.62	0.08
-161	5 ¹ / ₂	5 ¹¹ / ₁₆	3 ₃₂	5.487	.035	.103	.003	139.37	0.89	2.62	0.08
-162	5 ³ / ₄	5 ¹⁵ / ₁₆	3 ₃₂	5.737	.035	.103	.003	145.72	0.89	2.62	0.08
-163	6	6 ³ / ₁₆	3 ₃₂	5.987	.035	.103	.003	152.07	0.89	2.62	0.08
-164	6 ¹ / ₄	6 ⁷ / ₁₆	3 ₃₂	6.237	.040	.103	.003	158.42	1.02	2.62	0.08
-165	6 ¹ / ₂	6 ¹¹ / ₁₆	3 ₃₂	6.487	.040	.103	.003	164.77	1.02	2.62	0.08
-166	6 ³ / ₄	6 ¹⁵ / ₁₆	3 ₃₂	6.737	.040	.103	.003	171.12	1.02	2.62	0.08
-167	7	7 ³ / ₁₆	3 ₃₂	6.987	.040	.103	.003	177.47	1.02	2.62	0.08
-168	7 ¹ / ₄	7 ⁷ / ₁₆	3 ₃₂	7.237	.045	.103	.003	183.82	1.14	2.62	0.08
-169	7 ¹ / ₂	7 ¹¹ / ₁₆	3 ₃₂	7.487	.045	.103	.003	190.17	1.14	2.62	0.08
-170	7 ³ / ₄	7 ¹⁵ / ₁₆	3 ₃₂	7.737	.045	.103	.003	196.52	1.14	2.62	0.08
-171	8	8 ³ / ₁₆	3 ₃₂	7.987	.045	.103	.003	202.87	1.14	2.62	0.08
-172	8 ¹ / ₄	8 ⁷ / ₁₆	3 ₃₂	8.237	.050	.103	.003	209.22	1.27	2.62	0.08
-173	8 ¹ / ₂	8 ¹¹ / ₁₆	3 ₃₂	8.487	.050	.103	.003	215.57	1.27	2.62	0.08
-174	8 ³ / ₄	8 ¹⁵ / ₁₆	3 ₃₂	8.737	.050	.103	.003	221.92	1.27	2.62	0.08

O-RING STANDARD SIZE (AS568)

AS 568A UNIVERSAL DASH NUMBERS	NOMINAL SIZE			STANDARD O-RING SIZE				METRIC O-RING SIZE			
	INCHES			INCHES				MILLIMETERS			
	I.D.	O.D.	W.	I.D.	±	W.	±	I.D.	±	W.	±
-175	9	9 ³ / ₁₆	3 ³ / ₃₂	8.987	.050	.103	.003	228.27	1.27	2.62	0.08
-176	9 ¹ / ₄	9 ⁷ / ₁₆	3 ³ / ₃₂	9.237	.055	.103	.003	234.62	1.40	2.62	0.08
-177	9 ¹ / ₂	9 ¹¹ / ₁₆	3 ³ / ₃₂	9.487	.055	.103	.003	240.97	1.40	2.62	0.08
-178	9 ³ / ₄	9 ¹⁵ / ₁₆	3 ³ / ₃₂	9.737	.055	.103	.003	247.32	1.40	2.62	0.08
-201	3 ³ / ₁₆	7 ¹ / ₁₆	1 ¹ / ₈	.171	.055	.139	.004	4.34	0.13	3.53	0.10
-202	1 ¹ / ₄	1 ¹ / ₂	1 ¹ / ₈	.234	.005	.139	.004	5.94	0.13	3.53	0.10
-203	5 ¹ / ₁₆	9 ¹ / ₁₆	1 ¹ / ₈	.296	.005	.139	.004	7.52	0.13	3.53	0.10
-204	3 ³ / ₈	5 ⁵ / ₈	1 ¹ / ₈	.359	.005	.139	.004	9.12	0.13	3.53	0.10
-205	7 ¹ / ₁₆	1 ¹ / ₁₆	1 ¹ / ₈	.421	.005	.139	.004	10.69	0.13	3.53	0.10
-206	1 ¹ / ₂	3 ³ / ₄	1 ¹ / ₈	.484	.005	.139	.004	12.29	0.13	3.53	0.10
-207	9 ¹ / ₁₆	1 ³ / ₁₆	1 ¹ / ₈	.546	.007	.139	.004	13.87	0.18	3.53	0.10
-208	5 ⁵ / ₈	7 ⁷ / ₈	1 ¹ / ₈	.609	.009	.139	.004	15.47	0.23	3.53	0.10
-209	1 ¹ / ₁₆	1 ⁵ / ₁₆	1 ¹ / ₈	.671	.010	.139	.004	17.04	0.23	3.53	0.10
-210	3 ³ / ₄	1	1 ¹ / ₈	.734	.010	.139	.004	18.64	0.25	3.53	0.10
-211	1 ³ / ₁₆	1 ¹ / ₁₆	1 ¹ / ₈	.796	.010	.139	.004	20.22	0.25	3.53	0.10
-212	7 ⁷ / ₈	1 ¹ / ₈	1 ¹ / ₈	.859	.010	.139	.004	21.82	0.25	3.53	0.10
-213	1 ⁵ / ₁₆	1 ³ / ₁₆	1 ¹ / ₈	.921	.010	.139	.004	23.39	0.25	3.53	0.10
-214	1	1 ¹ / ₄	1 ¹ / ₈	.984	.010	.139	.004	24.99	0.25	3.53	0.10
-215	1 ¹ / ₁₆	1 ⁵ / ₁₆	1 ¹ / ₈	1.046	.010	.139	.004	26.57	0.25	3.53	0.10
-216	1 ¹ / ₈	1 ³ / ₈	1 ¹ / ₈	1.109	.012	.139	.004	28.17	0.30	3.53	0.10
-217	1 ³ / ₁₆	1 ⁷ / ₁₆	1 ¹ / ₈	1.171	.012	.139	.004	29.74	0.30	3.53	0.10
-218	1 ¹ / ₄	1 ¹ / ₂	1 ¹ / ₈	1.234	.012	.139	.004	31.34	0.30	3.53	0.10
-219	1 ⁵ / ₁₆	1 ⁹ / ₁₆	1 ¹ / ₈	1.296	.012	.139	.004	32.92	0.30	3.53	0.10
-220	1 ³ / ₈	1 ⁵ / ₈	1 ¹ / ₈	1.359	.012	.139	.004	34.52	0.30	3.53	0.10
-221	1 ⁷ / ₁₆	1 ¹¹ / ₁₆	1 ¹ / ₈	1.421	.012	.139	.004	36.09	0.30	3.53	0.10
-222	1 ¹ / ₂	1 ³ / ₄	1 ¹ / ₈	1.484	.015	.139	.004	37.69	0.38	3.53	0.10
-223	1 ⁵ / ₈	1 ⁷ / ₈	1 ¹ / ₈	1.609	.015	.139	.004	40.87	0.38	3.53	0.10
-224	1 ³ / ₄	2	1 ¹ / ₈	1.734	.015	.139	.004	44.04	0.38	3.53	0.10
-225	1 ⁷ / ₈	2 ¹ / ₈	1 ¹ / ₈	1.859	.018	.139	.004	47.22	0.46	3.53	0.10
-226	2	2 ¹ / ₄	1 ¹ / ₈	1.984	.018	.139	.004	50.39	0.46	3.53	0.10
-227	2 ¹ / ₁₆	2 ³ / ₈	1 ¹ / ₈	2.109	.018	.139	.004	53.57	0.46	3.53	0.10
-228	2 ¹ / ₄	2 ¹ / ₂	1 ¹ / ₈	2.234	.020	.139	.004	56.74	0.51	3.53	0.10
-229	2 ³ / ₈	2 ⁵ / ₈	1 ¹ / ₈	2.359	.020	.139	.004	59.92	0.51	3.53	0.10
-230	2 ¹ / ₂	2 ³ / ₄	1 ¹ / ₈	2.484	.020	.139	.004	63.09	0.51	3.53	0.10
-231	2 ⁵ / ₈	2 ⁷ / ₈	1 ¹ / ₈	2.609	.020	.139	.004	66.27	0.51	3.53	0.10
-232	2 ³ / ₄	3	1 ¹ / ₈	2.734	.024	.139	.004	69.44	0.61	3.53	0.10
-233	2 ⁷ / ₈	3 ¹ / ₈	1 ¹ / ₈	2.859	.024	.139	.004	72.62	0.61	3.53	0.10
-234	3	3 ¹ / ₄	1 ¹ / ₈	2.984	.024	.139	.004	75.79	0.61	3.53	0.10
-235	3 ¹ / ₈	3 ³ / ₈	1 ¹ / ₈	3.109	.024	.139	.004	78.97	0.61	3.53	0.10
-236	3 ¹ / ₄	3 ¹ / ₂	1 ¹ / ₈	3.234	.024	.139	.004	82.14	0.61	3.53	0.10
-237	3 ³ / ₈	3 ⁵ / ₈	1 ¹ / ₈	3.359	.024	.139	.004	85.32	0.61	3.53	0.10

O-RING STANDARD SIZE (AS568)

AS 568A UNIVERSAL DASH NUMBERS	NOMINAL SIZE			STANDARD O-RING SIZE				METRIC O-RING SIZE			
	INCHES			INCHES				MILLIMETERS			
	I.D.	O.D.	W.	I.D.	±	W.	±	I.D.	±	W.	±
-238	3½	3¾	⅛	3.484	.024	.139	.004	88.49	0.61	3.53	0.10
-239	3⅝	3⅞	⅛	3.609	.028	.139	.004	91.67	0.71	3.53	0.10
-240	3¾	4	⅛	3.734	.028	.139	.004	94.84	0.71	3.53	0.10
-241	3⅞	4⅛	⅛	3.859	.028	.139	.004	98.02	0.71	3.53	0.10
-242	4	4¼	⅛	3.984	.028	.139	.004	101.19	0.71	3.53	0.10
-243	4⅛	4⅜	⅛	4.109	.028	.139	.004	104.37	0.71	3.53	0.10
-244	4¼	4½	⅛	4.234	.030	.139	.004	107.54	0.76	3.53	0.10
-245	4⅜	4⅝	⅛	4.359	.030	.139	.004	110.72	0.76	3.53	0.10
-246	4½	4¾	⅛	4.484	.030	.139	.004	113.89	0.76	3.53	0.10
-247	4⅝	4⅞	⅛	4.609	.030	.139	.004	117.07	0.76	3.53	0.10
-248	4¾	5	⅛	4.734	.030	.139	.004	120.24	0.76	3.53	0.10
-249	4⅞	5⅛	⅛	4.859	.035	.139	.004	123.42	0.89	3.53	0.10
-250	5	5¼	⅛	4.984	.035	.139	.004	126.59	0.89	3.53	0.10
-251	5⅛	5⅜	⅛	5.109	.035	.139	.004	129.77	0.89	3.53	0.10
-252	5¼	5½	⅛	5.234	.035	.139	.004	132.94	0.89	3.53	0.10
-253	5⅜	5⅝	⅛	5.359	.035	.139	.004	136.12	0.89	3.53	0.10
-254	5½	5¾	⅛	5.484	.035	.139	.004	139.29	0.89	3.53	0.10
-255	5⅝	5⅞	⅛	5.609	.035	.139	.004	142.47	0.89	3.53	0.10
-256	5¾	6	⅛	5.734	.035	.139	.004	145.64	0.89	3.53	0.10
-257	5⅞	6⅛	⅛	5.859	.035	.139	.004	148.82	0.89	3.53	0.10
-258	6	6¼	⅛	5.984	.035	.139	.004	151.99	0.89	3.53	0.10
-259	6¼	6½	⅛	6.234	.040	.139	.004	158.34	1.02	3.53	0.10
-260	6½	6¾	⅛	6.484	.040	.139	.004	164.69	1.02	3.53	0.10
-261	6¾	7	⅛	6.734	.040	.139	.004	171.04	1.02	3.53	0.10
-262	7	7¼	⅛	6.984	.040	.139	.004	177.39	1.02	3.53	0.10
-263	7¼	7½	⅛	7.234	.045	.139	.004	183.74	1.14	3.53	0.10
-264	7½	7¾	⅛	7.484	.045	.139	.004	190.09	1.14	3.53	0.10
-265	7¾	8	⅛	7.734	.045	.139	.004	196.44	1.14	3.53	0.10
-266	8	8¼	⅛	7.984	.045	.139	.004	202.79	1.14	3.53	0.10
-267	8¼	8½	⅛	8.234	.050	.139	.004	209.14	1.27	3.53	0.10
-268	8½	8¾	⅛	8.484	.050	.139	.004	215.49	1.27	3.53	0.10
-269	8¾	9	⅛	8.734	.050	.139	.004	221.84	1.27	3.53	0.10
-270	9	9¼	⅛	8.984	.050	.139	.004	228.19	1.27	3.53	0.10
-271	9¼	9½	⅛	9.234	.055	.139	.004	234.54	1.40	3.53	0.10
-272	9½	9¾	⅛	9.484	.055	.139	.004	240.89	1.40	3.53	0.10
-273	9¾	10	⅛	9.734	.055	.139	.004	247.24	1.40	3.53	0.10
-274	10	10¼	⅛	9.984	.055	.139	.004	253.59	1.40	3.53	0.10
-275	10½	10¾	⅛	10.484	.055	.139	.004	266.29	1.40	3.53	0.10
-276	11	11¼	⅛	10.984	.065	.139	.004	278.99	1.65	3.53	0.10
-277	11½	11¾	⅛	11.484	.065	.139	.004	291.69	1.65	3.53	0.10
-278	12	12¼	⅛	11.984	.065	.139	.004	304.39	1.65	3.53	0.10

O-RING STANDARD SIZE (AS568)

AS 568A UNIVERSAL DASH NUMBERS	NOMINAL SIZE			STANDARD O-RING SIZE				METRIC O-RING SIZE			
	INCHES			INCHES				MILLIMETERS			
	I.D.	O.D.	W.	I.D.	±	W.	±	I.D.	±	W.	±
-279	13	13 ¹ / ₄	1/8	12.984	.065	.139	.004	329.79	1.65	3.53	0.10
-280	14	14 ¹ / ₄	1/8	13.984	.065	.139	.004	355.19	1.65	3.53	0.10
-281	15	15 ¹ / ₄	1/8	14.984	.065	.139	.004	380.59	1.65	3.53	0.10
-282	16	16 ¹ / ₄	1/8	15.955	.075	.139	.004	405.26	1.91	3.53	0.10
-283	17	17 ¹ / ₄	1/8	16.955	.080	.139	.004	430.66	2.03	3.53	0.10
-284	18	18 ¹ / ₄	1/8	17.955	.085	.139	.004	456.06	2.16	3.53	0.10
-309	7/16	13/16	3/16	.412	.005	.210	.005	10.46	0.13	5.33	0.13
-310	1/2	7/8	3/16	.475	.005	.210	.005	12.07	0.13	5.33	0.13
-311	9/16	15/16	3/16	.537	.007	.210	.005	13.64	0.18	5.33	0.13
-312	5/8	1	3/16	.600	.009	.210	.005	15.24	0.23	5.33	0.13
-313	11/16	1 1/16	3/16	.662	.009	.210	.005	16.81	0.23	5.33	0.13
-314	3/4	1 1/8	3/16	.725	.010	.210	.005	18.42	0.25	5.33	0.13
-315	13/16	1 3/16	3/16	.787	.010	.210	.005	19.99	0.25	5.33	0.13
-316	7/8	1 1/4	3/16	.850	.010	.210	.005	21.59	0.25	5.33	0.13
-317	15/16	1 5/16	3/16	.912	.010	.210	.005	23.16	0.25	5.33	0.13
-318	1	1 3/8	3/16	.975	.010	.210	.005	24.77	0.25	5.33	0.13
-319	1 1/16	1 7/16	3/16	1.037	.010	.210	.005	26.34	0.25	5.33	0.13
-320	1 1/8	1 1/2	3/16	1.100	.012	.210	.005	27.94	0.30	5.33	0.13
-321	1 3/16	1 9/16	3/16	1.162	.012	.210	.005	29.51	0.30	5.33	0.13
-322	1 1/4	1 5/8	3/16	1.225	.012	.210	.005	31.12	0.30	5.33	0.13
-323	1 5/16	1 11/16	3/16	1.287	.012	.210	.005	32.69	0.30	5.33	0.13
-324	1 3/8	1 3/4	3/16	1.350	.012	.210	.005	34.29	0.30	5.33	0.13
-325	1 1/2	1 7/8	3/16	1.475	.015	.210	.005	37.47	0.38	5.33	0.13
-326	1 5/8	2	3/16	1.600	.015	.210	.005	40.64	0.38	5.33	0.13
-327	1 3/4	2 1/8	3/16	1.725	.015	.210	.005	43.82	0.38	5.33	0.13
-328	1 7/8	2 1/4	3/16	1.850	.015	.210	.005	46.99	0.38	5.33	0.13
-329	2	2 3/8	3/16	1.975	.018	.210	.005	50.17	0.46	5.33	0.13
-330	2 1/8	2 1/2	3/16	2.100	.018	.210	.005	53.34	0.46	5.33	0.13
-331	2 1/4	2 5/8	3/16	2.225	.018	.210	.005	56.52	0.46	5.33	0.13
-332	2 3/8	2 3/4	3/16	2.350	.018	.210	.005	59.69	0.46	5.33	0.13
-333	2 1/2	2 7/8	3/16	2.475	.020	.210	.005	62.87	0.51	5.33	0.13
-334	2 5/8	3	3/16	2.600	.020	.210	.005	66.04	0.51	5.33	0.13
-335	2 3/4	3 1/8	3/16	2.725	.020	.210	.005	69.22	0.51	5.33	0.13
-336	2 7/8	3 1/4	3/16	2.850	.020	.210	.005	72.39	0.51	5.33	0.13
-337	3	3 3/8	3/16	2.975	.024	.210	.005	75.57	0.61	5.33	0.13
-338	3 1/8	3 1/2	3/16	3.100	.024	.210	.005	78.74	0.61	5.33	0.13
-339	3 1/4	3 5/8	3/16	3.225	.024	.210	.005	81.92	0.61	5.33	0.13
-340	3 3/8	3 3/4	3/16	3.350	.024	.210	.005	85.09	0.61	5.33	0.13
-341	3 1/2	3 7/8	3/16	3.475	.024	.210	.005	88.27	0.61	5.33	0.13
-342	3 5/8	4	3/16	3.600	.028	.210	.005	91.44	0.71	5.33	0.13
-343	3 3/4	4 1/8	3/16	3.725	.028	.210	.005	94.62	0.71	5.33	0.13